

VOLTO		Large series									Compact series				
		1300 T	1100 T	1100	900 T	900	800 T	800	700	80	65	60	55	45	
Dimensions and weights															
Working width	m	13.00	10.70	10.70	8.70	8.70	7.70	7.70	6.70	7.70	6.40	5.80	5.20	4.50	
Height when parked	m	3.70	3.99	3.80	3.65	3.45	3.55	3.40	3.50	3.39	3.46	3.09	2.56	2.41	
Transport width	m	2.98	2.98	2.98	2.98	2.98	2.98	2.98	2.97	2.93	2.75	2.50	2.75	2.75	
Transport length	m	6.06	4.22	–	4.22	–	4.22	–	–	–	–	–	–	–	
Mounting	Cat.	II	II	II	II	II	II	II	II	II	I+II	II	I+II	I+II	
Weight according to spec.	kg	2420	1780	1480	1440	1140	1240	980	890	910	710	720	560	540	
Drive line															
PTO shaft speed	rpm	1000	540	540	540	540	540	540	540	540	540	540	540	540	
PERMALINK		●	●	●	●	●	●	●	●	●	●	●	●	●	
Maintenance-free transmission		●	●	●	●	●	●	●	●	–	–	–	–	–	
Rotors															
Rotors	Qty	10	10	10	8	8	6	6	6	8	6	6	4	4	
Rotor diameter	m	1.70	1.50	1.50	1.50	1.50	1.70	1.70	1.50	1.30	1.50	1.30	1.70	1.50	
Spreader arms per rotor	Qty	7	6	6	6	6	7	7	6	5	6	5	6	6	
MAX SPREAD crop flow concept		●	●	●	●	●	●	●	●	●	●	●	●	●	
Spreading angle	degrees	12/16	12/16	12/16	12/16	12/16	12/16	12/16	12/16	14.5/18	12/16	14.5/18	12/16	12/16	
Tine overrun	degrees	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	– 7/0/+ 7	
Convenience															
CLAAS power drawbar (CKL)		–	–	●	–	●	–	●	●	●	●	●	●	●	
Guide wheel		–	○	○	○	○	○	○	○	○	○	○	○	○	
Double castor guide wheel		●	–	–	–	–	–	–	–	–	–	–	–	–	
Headland lift		○ ¹	○	○	○	○	●	●	●	○	●	●	●	●	
Edge-tedding crop guard		○	○	○	○	○	○	○	○	○	○	○	○	○	
Overnight swath gearbox		Speed changeover to 540 rpm	○	○	○	○	○	○	○	○	○	○	○	○	
Spare wheel		○	○	○	○	○	○	○	○	○	○	○	○	○	
Hydraulic connections															
Folding		1 × da	1 × sa + 1 × da	1 × sa + 1 × da	1 × da	1 × da	1 × da	1 × da	1 × sa	1 × da	1 × sa	1 × sa	1 × sa	1 × sa	
Hydraulic edge-tedding crop guard (optional)		1 × sa (+1 × da ¹)	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × da	1 × sa	1 × sa	
Tyres															
16 x 6.5–8		6	8	8	6	6	6	6	6	8	6	6	4	4	
18.5 x 8.5–8		4	2	2	2	2	–	–	–	–	–	–	–	–	
215/65–15		–	–	–	2	–	2	–	–	–	–	–	–	–	
10.00/75–15.3		2	2	–	–	–	–	–	–	–	–	–	–	–	
Guide wheel tyres															
16 x 6.5–8 10 PR		–	–	○	–	○	–	○	○	○	○	○	○	○	
18.5 x 8.5–8		●	○	–	○	–	○	–	–	–	–	–	–	–	

¹ For headlands lift + 1 × da

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.