

	DISCO ¹	3600 FRC MOVE	3600 FC MOVE	3600 F MOVE	3200 FRC MOVE	3200 FC MOVE	3200 F MOVE	3600 FRC PROFIL	3600 FC PROFIL	3600 F PROFIL	3200 FRC PROFIL	3200 FC PROFIL	3200 F PROFIL	3150 F	4000 CONTOUR	3600 RC CONTOUR	3600 / 3600 C CONTOUR	3200 RC CONTOUR	3200 / 3200 C CONTOUR	2800 RC CONTOUR	2800 / 2800 C CONTOUR	3550	3150 C	3150	2750 RC	2750 C	2750	290	250	210 RC	210	
Segadoras frontales														Segadoras traseras CONTOUR con enganche central						Segadoras traseras con enganche lateral						Segadoras traseras con barra Inline						
Pesos y medidas																																
Anchura de trabajo	m	3,40	3,40	3,40	3,00	3,00	3,00	3,00	3,40	3,40	3,00	3,00	3,00	3,00	3,80	3,40	3,40	3,00	3,00	2,60	2,60	3,40	3,00	3,00	2,60	2,60	2,60	2,85	2,45	2,10	2,10	
Categoría de acoplamiento		II	II	II	II	II	II	II	II	II	II	II	II	III	III	II / III	III	II / III	II	II	II	II	II	II	II	II	II	II	II	II		
Rég. de rev. toma de fuerza	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	540 (460)	540 (460)	540 (460)	540	540	540	540		
Anchura de transporte	m	3,40	3,40	3,40	3,00	3,00	3,00	3,40	3,40	3,40	3,00	3,00	3,00	3,00	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Altura de la máquina	m	–	–	–	–	–	–	–	–	–	–	–	–	3,90	3,57	3,57	3,19	3,19	2,86	2,86	3,87	3,70	3,70	3,29	3,29	3,29	3,40	3,00	2,65	2,65		
Peso (dependiendo del acondicionador)	kg aprox.	1420	1390	1060	1250	1220	970	685	1195	870	1040	1010	775	685	1040	1300	950 / 1280	1180	870 / 1150	1070	810 / 1050	845	1130	785	1060	1040	725	630	600	880	560	
Segadora																																
Barra de corte MAX CUT ²		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–		
Descarga ACTIVE FLOAT		● ³	● ³	● ³	● ³	● ³	● ³	○ ³	○ ³	○ ³	○ ³	○ ³	○ ³	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–		
Discos (2 cuchillas por disco)		8	8	8	7	7	7	8	8	8	7	7	7	7	9	8	8	7	7	6	6	8	7	7	6	6	6	7	6	5	5	
Cambio rápido de cuchillas		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–		
Acondicionador																																
Rég. de rev. acondicionador	rpm	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	–	–	940	– / 910	940	– / 910	940	– / 910	–	900	–	900	900	–	–	–	940	–	
Instalación hidráulica																																
Distribuidores hidráulicos		1 es (+1 ed ⁴ + 1es ³)						(1 ed ⁴ + 1 es ³)						1 x ed ⁵ (+1 ed ⁴ +1 es ³)				1 x ed ⁵ (+ 1 x es ³)						1 x es								
Equipamiento																																
Petos protectores plegables hidr.		○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	–	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Capota de esparcido ancho		–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	– / ○	–	– / ○	–	– / ○	–	○	–	–	○	–	–	–	–	–	
Chapas hileradoras regulables		●	●	–	●	●	–	●	●	–	●	●	–	–	–	●	– / ●	●	– / ●	●	– / ●	–	●	–	●	●	–	–	–	●	–	
Disco hilerador exterior		–	–	● (2 x)	–	–	● (1 x)	–	–	● (2 x)	–	–	● (1 x)	● (1 x)	○	–	○ / –	–	○ / –	–	○ / –	○	–	○	–	–	○	–	–	–	–	
Patines de corte alto		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Patines dobles de corte alto		○	○	○	○	○	○	○	○	○	○	○	○	–	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	
Patines antidesgaste		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Protección de la barra (para uso intensivo)		○	○	○	○	○	–	○	○	○	○	○	–	–	–	○	– / ○	○	– / ○	○	– / ○	–	–	–	–	–	–	–	–	–	–	
Rótulos de advertencia con iluminación		○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○	○	○	○	○	○	○	○	○	○	○	○	○	○	–	–	–	–	
Espejo doble		○	○	○	○	○	○	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Empestillamiento hidr. de transporte		–	–	–	–	–	–	–	–	–	–	–	–	–	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	
Seguro mecánico anti-choque		–	–	–	–	–	–	–	–	–	–	–	–	–	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	

¹ C = acondicionador de púas, RC = acondicionador de rodillos, F = frontal, T = arrastrada, sin suplemento = sin acondicionador

² Altura de corte estándar 40 mm (ajustable sin escalonamientos, 30–70 mm)

³ 1 x es necesario para el ajuste de la presión ACTIVE FLOAT

⁴ 1 x ed necesario para el plegado hidráulico de la lona protectora

⁵ Con posición flotante

⁶ Plegable

3600 TRC CONTOUR	3600 TC CONTOUR	3200 TRC CONTOUR	3200 TC CONTOUR	3200 TC AUTOSWATHER	3150 TRC	3150 TC	3150 TC FLAPGROUPER
---------------------	--------------------	---------------------	--------------------	------------------------	----------	---------	------------------------

**Segadoras arrastradas
con lanza central CONTOUR**

3,40	3,40	3,00	3,00	3,00	3,00	3,00	3,00
1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)
3,40	3,40	3,00	3,00	3,00	3,00	3,00	3,00
-	-	-	-	-	-	-	-
2380	2320	2300	2230	2430	1900	1750	1900

**Segadoras arrastradas
con lanza lateral**

●	●	●	●	●	●	●	●
●	●	●	●	●	-	-	-
8	8	7	7	7	7	7	7
●	●	●	●	●	●	●	●

1050	1080 / 900	1050	1080 / 900	1200	1033	900/770	1033
------	---------------	------	---------------	------	------	---------	------

1 x es + 1 x ed (+ 1 x es ³)	2 x es + 1 x ed (+ 1 x es ³)	1 x es + 1 x ed
------------------------------------------	------------------------------------------------	-----------------

-	-	-	-	-	-	-	-
-	○	-	○	○	-	○	-
●	●	●	●	●	●	●	●
-	-	-	-	-	-	-	-
○	○	○	○	○	○	○	○
-	-	-	-	-	-	-	-
○	○	○	○	○	○	○	○
○	○	○	○	○	-	-	-
●	●	●	●	●	●	●	●
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-